

DCN-FCS Flush Channel Selector





- Stylish and modern design (IF award)
- ► Automatically adapts to available channels
- ► Built-in "Silent" function
- No audio output until the headphone is connected
- Flush mountable in tabletops, on top or at the front, or in arm rests of seats

The Flush Channel Selector is a compact and stylish singleuser audio channel selector for listening by headphone. It provides a choice of up to 32 high-quality audio channels used for distribution of interpretation and floor channels.

Functions

- Built-in "Silent" function; no audio output until one of the keys has been pressed to eliminate audible noise from the headphones when not in use
- Upon insertion of a headphone the default "floor" channel (channel 0) is selected with a comfortable headphone volume and the dimmed backlighting is activated

Controls and Indicators

- Two push-buttons (up/down) for channel selection
- Two push-buttons (up/down) for headphone volume control
- Backlit 2-digit LCD for channel number indication Interconnection

Interconnections

- 3.5 mm (0.14 in) stereo jack headphone connector
- · Connector for external headphone
- 2 m (78.7 in) cable with a molded six-pole circular connector

Six-pole circular connector for loop-through interconnection

Certifications and Approvals

Region	Certification
Europe	CE

Technical Specifications

DCN-FCS-D

Electrical Frequency response 30 Hz - 20 kHz Headphone Load > 32 ohm < 1 k ohm impedance Output power 2 x 15 mW/32 ohm Mechanical Flush mounted Mounting Dimensions (H x W x D) 40 x 100 x 100 mm $(1.6 \times 3.9 \times 3.9 \text{ in})$ Weight 0.3 kg (0.66 lb)Color DCN-FCS Silver (RAL 9022)

Dark (graphite gray)

Ordering Information		
DCN-FCS Flush Channel Selector flush mounted, silver	DCN-FCS	
DCN-FCS-D Flush Channel Selector Dark flush mounted, dark	DCN-FCS-D	
Accessories		
LBB 3443/00 Lightweight Headphones high quality sound reproduction, lightweight, replaceable ear pads and normal cable	LBB3443/00	
LBB 3443/10 Lightweight Headphones Durable Cable high quality sound reproduction, lightweight, replaceable ear pads and durable cable	LBB3443/10	
LBB 3441/10 Under the Chin Headphones with 1.2 m (4 ft) cable terminated with 3.5 mm (0.14 in) right-angled stereo jack plug	LBB3441/10	
LBB 3442/00 Single Earphone Lightweight single earphone, 2 m (4 ft) cable terminated with 3.5 mm (0.14 in) jack plug	LBB3442/00	
LBB 3015/04 High Quality Dynamic Headphones Durable, dynamic headphones.	LBB3015/04	
DCN-TTH Table Top Housing (10 pcs) to hold flush mount units, charcoal, set of 10	DCN-TTH	

Americas:
Bosch Security Systems, Inc.
Communications Systems
12000 Portland Avenue, South
Burnsville, Minnesota 55337, USA
Phone: +1-800-392-3497
Fax: +1-800-955-6831
audiosupport@US.bosch.com
www.boschcommunications.us

Europe, Middle East, Africa: Bosch Security Systems B.V. P.O. Box 80002 5600 JB Eindhoven, The Netherlands Phone: + 31 40 2577 284 Fax: +31 40 2577 330 emea.securitysystems@bosch.com www.boschsecurity.com

Asia-Pacific: Rep Robert Bosch (SEA) Pte Ltd, Security Systems 38C Jalan Pemimpin Singapore 577180 Phone: +65 6319 3453 Fax: +65 6319 3499 apr.securitysystems@bosch.com www.boschsecurity.com Represented by